

Claims

1. A wheeled trunk **10** having handle **11** for being dragged on the ground, comprising on the lid **12** thereof a plurality of spaced hooks **13** capable of interconnecting with corresponding loops **22** fitted at the periphery of a bag **20** matching the wheeled trunk **10** whereby enabling the bag **20** attached temporarily to the lid **12** of the wheeled trunk **10**; the opening of each hook **13** is disposed substantially in the reverse direction to the area enclosed by the hooks **13**.
2. The wheeled trunk **10** of claim 1, wherein substantially each of the hooks **13** is fitted in a concavity **121** formed on the lid **12** of the wheeled trunk **10**.
3. The wheeled trunk **10** of claim 1, wherein each of the hooks **13** further comprises a barb **131**.
4. The wheeled trunk **10** of claim 1, wherein each of the hooks **13** further comprises at least a through hole **132**.
5. A bag **20** having at its periphery a plurality of loops **22** capable of interconnecting with corresponding hooks **13** fixed on the lid **12** of a wheeled trunk **10** matching the bag **20** whereby enabling the bag **20** attached temporarily to the lid **12** of the wheeled trunk **10**.
6. The bag **20** of claim 5, wherein at least one of the loops **22** is elastic and generates restoring tension when it is elongated.